

LEVEL TRANSMITTERS

Keller America offers a variety of submersible level transmitters designed to meet the changing demands in the level measurement applications you may encounter. Keller combines proven pressure measurement technology with state-of-the-art electronics to provide outstanding reliability and accuracy over temperature.

This reference provides an overview of the submersible level measurement products Keller offers. For more detailed specifications, click on the product name to be directed to the product-specific datasheet. If you have any questions, or would like to discuss your particular application in more detail, contact Keller America today!



LEVELGAGE - General purpose submersible level transmitter

±1% FS TEB standard accuracy (±0.5% FS TEB optional) Custom ranges from 0...3ftWC to 0...900ftWC 4...20mA, 0...5VDC, or 0...10VDC analog outputs Guaranteed lightning protection on 4...20mA models 2 year parts and workmanship warranty 3-day lead time



LEVELRAT - Non-fouling submersible level transmitter

±1% FS TEB standard accuracy
Custom ranges from 0...5ftWC to 0...100ftWC
4...20mA, 0...5VDC, or 0...10VDC analog outputs
Guaranteed lightning protection on 4...20mA models
2 year parts and workmanship warranty
3-day lead time



ACCULEVEL - High accuracy digital submersible level transmitter

±0.25% FS TEB standard accuracy (±0.1% FS TEB optional)
Custom ranges from 0...3ftWC to 0...900ftWC
4...20mA, 0...5VDC, or 0...10VDC analog outputs + RS485 digital output
Guaranteed lightning protection on 4...20mA models
2 year parts and workmanship warranty
3-day lead time

KELLER AMERICA INC

Submersible

LEVEL TRANSMITTERS



MICROLEVEL - Micro-bore submersible level transmitter

0.63" O.D.

±0.25% FS TEB standard accuracy (±0.1% FS TEB optional)

Custom ranges from 0...3ftWC to 0...900ftWC

4...20mA analog output + RS485 digital output

2 year parts and workmanship warranty

3-day lead time



NANOLEVEL - High accuracy, low level submersible level transmitter

±0.25% FS TEB standard accuracy (±0.1% FS TEB optional)

Custom ranges from 0...4 inWC to 0...120inWC

4...20mA analog output + RS485 digital output

2 year parts and workmanship warranty

3-day lead time



DIGILEVEL - SDI-12 convertible level transmitter

±0.1% FS TEB standard accuracy (Opt. accuracy meets USGS OSW spec)

Custom ranges from 0...3 ftWC to 0...900 ftWC SDI-12 digital output

2 year parts and workmanship warranty

Emulate modes enable extended commands from other SDI-12 transmitters



ECONOLEVEL - OEM submersible level transmitter

±1% FS TEB standard accuracy (±0.5% FS TEB optional)

Available ranges: 0...11.5ftWC, 0...34.5ftWC, 0...115.5ftWC, and 0...231ftWC

4...20mA analog output

1 year parts and workmanship warranty

25 PIECE MINIMUM ORDER QUANTITY

KELLER AMERICA INC