Pressure

TRANSMITTERS

Keller America offers a variety of pressure transmitters designed to meet the changing demands in the pressure measurement applications you may encounter. Keller combines proven pressure measurement technology with state-of-the-art electronics to provide outstanding reliability and accuracy over temperature.

This reference provides an overview of the pressure transmitters Keller offers. For more detailed specifications, click on the product name to be directed to the product-specific datasheet. If you have any questions, or would like to discuss your particular application in more detail, contact Keller America today!



ECONOLINE - General purpose pressure transmitter

±1% FS static accuracy standard (±0.5% FS optional) Available 0...15, 50, 100, 300, 500, 1000, 3000, 5000 & 10K psi ranges 1/4"-18 male pressure connection Available cable or mPm393 electrical connection 4...20mA or 0.5...4.5VDC analog outputs 1 year parts and workmanship warranty 3-day lead time



VALUELINE - High accuracy pressure transmitter

±0.25% FS TEB standard accuracy (±0.1% FS TEB optional) Custom ranges from 0...2 psi up to 0...15k psi 1/4"-18 male pressure connection Available cable or DIN43650 (MIL-C-26482 opt.) electrical connections 4...20mA, 0...5VDC or 0...10VDC analog outputs Guaranteed lightning protection on 4...20mA models 2 year parts and workmanship warranty 3-day lead time



PRECISELINE - High accuracy pressure transmitter

±0.25% FS TEB standard accuracy (±0.1% FS TEB optional) Custom ranges from 0...2 psi up to 0...15k psi 1/4"-18 male pressure connection Available cable or DIN43650 (MIL-C-26482 opt.) electrical connections 4...20mA, 0...5VDC or 0...10VDC analog + RS485 digital outputs Guaranteed lightning protection on 4...20mA models 2 year parts and workmanship warranty 3-day lead time

KELLER AMERICA INC

351 BELL KING ROAD · NEWPORT NEWS, VA 23606 · TOLL FREE 877-253-5537 · PHONE (757) 596-6680 · FAX (757) 596-6659 EMAIL SALES@KELLERAMERICA.COM · WEBSITE WWW.KELLERAMERICA.COM

Pressure

TRANSMITTERS



SERIES 21Y - Compact pressure transmitter

±1% FS TEB accuracy Custom ranges from 0...30psi to 0...15000 psi 4...20mA, 0...10VDC or 0.5...4.5VDC analog outputs

SERIES 21C - Compact pressure transmitter

±1% FS TEB accuracy Custom ranges from 0...30psi to 0...1500 psi 0.5...4.5VDC ratiometric analog or I²C digital outputs

Ei SERIES - Intrinsically safe pressure transmitters

±0.1% FS TEB standard accuracy Custom ranges from 0...2 psi up to 0...15k psi 4...20mA, 0...5VDC or 0...10VDC analog + RS485 digital outputs

Ed SERIES - Explosion proof pressure transmitters

±0.2% FS TEB standard accuracy Custom ranges from 0...2 psi up to 0...15k psi 4...20mA or 0...10VDC analog + RS485 digital outputs (33/35X Ed only)



HT/HTT SERIES - High temperature pressure transmitters

±0.2% FS TEB standard analog accuracy (±0.15% digital) 20...120°C compensated temperature range 4...20mA or 0...10VDC analog + RS485 digital outputs

HTC SERIES - Very high temperature pressure transmitters

±0.5% FS TEB accuracy 20...300°C compensated temperature range 4...20mA or 0...10VDC analog + RS485 digital outputs



PD-33X - High accuracy differential pressure transmitter

±0.15% FS TEB analog accuracy (± 0.1% FS TEB digital) Differential pressure ranges up to 30 Bar 4...20mA, 5VDC, 10VDC or 0.1...2.5 VDC analog + <u>RS485 digital outputs</u>

PD-39X - Differential pressure transmitter

±0.1% FS TEB accuracy Differential pressure ranges up to 300 Bar 4...20mA or 0...10VDC analog outputs + RS485 digital outputs

KELLER AMERICA INC

351 BELL KING ROAD · NEWPORT NEWS, VA 23606 · TOLL FREE 877-253-5537 · PHONE (757) 596-6680 · FAX (757) 596-6659 EMAIL SALES@KELLERAMERICA.COM · WEBSITE WWW.KELLERAMERICA.COM